

Breathable, switchable, transparent polyurethane/urethane/TPU film on paper carrier with a long history of use in medical applications



Breathable, switchable, transparent polyurethane/urethane/TPU film on paper carrier with a long history of use in medical applications

Typical Properties

Property	Typical Value
Stripping Load (Release) (gf/cm)	3
Thickness (Micron)	52
Weight (g/m ²)	62
MVTR, upright (g/m ² per 24hrs @37°C)	1700
MVTR, inverted (g/m ² per 24hrs @37°C)	9000
Tensile Strength MD (gf/cm)	1450
Tensile Strength TD (gf/cm)	1500
Nominal Length at max width (lm)	1000
Minimum Width (mm)	50
Maximum Width (mm)	1300
Carrier	70gsm single sided release paper
Liner	n/a
Adhesive	n/a
Other Information	switchable film
Elongation at break, MD (%)	510
Elongation at break, TD (%)	570

Product Information correct as of 7th March 2018

DelStar Technologies

Broad Lane Gilberdyke East Yorkshire HU15 2TD

<http://extrudedfilmsandnets.co.uk> +44 (0)1430 440757

© DelStar Technologies Limited 2018. Registered in England #4296794

[Terms Of Use](#) [Disclaimer](#) [Accessibility](#) [Cookie Policy](#)