

Transparent scrim reinforced polyurethane/urethane film on paper carrier with a long history of use in medical applications

RF60C

Transparent scrim reinforced polyurethane/urethane film on paper carrier with a long history of use in medical applications

Typical Properties

| Property | Typical Value |
|--|-----------------------------------|
| Thickness (Micron) | 110 |
| Weight (g/m ²) | 60 |
| MVTR, upright (g/m ² per 24hrs @37°C) | 900 |
| Tensile Strength MD (gf/cm) | 1400 |
| Tensile Strength TD (gf/cm) | 900 |
| Nominal Length at max width (lm) | 1000 |
| Minimum Width (mm) | 50 |
| Maximum Width (mm) | 1290 |
| Carrier | 100gsm single sided release paper |
| Liner | n/a |
| Adhesive | n/a |
| Other Information | Scrim reinforced |
| Stripping Load (Release) (gf/cm) | 1.3 |
| Elongation at break, MD (%) | 50 |
| Elongation at break, TD (%) | 30 |

Product Information correct as of 7th March 2018

DelStar Technologies

Broad Lane Gilberdyke East Yorkshire HU15 2TD

<http://extrudedfilmsandnets.co.uk> +44 (0)1430 440757

© DelStar Technologies Limited 2018. Registered in England #4296794

[Terms Of Use](#) [Disclaimer](#) [Accessibility](#) [Cookie Policy](#)