

Transparent scrim reinforced medical grade polyurethane/urethane film on paper carrier with high tack acrylic adhesive coating

**RF60C/A16**

Transparent scrim reinforced medical grade polyurethane/urethane film on paper carrier with high tack acrylic adhesive coating

**Typical Properties**

Property	Typical Value
Thickness (Micron)	110
Weight (g/m <sup>2</sup> )	60
MVTR, upright (g/m <sup>2</sup> per 24hrs @37°C)	440
Tensile Strength MD (gf/cm)	1400
Tensile Strength TD (gf/cm)	900
Nominal Length at max width (lm)	1000
Minimum Width (mm)	50
Maximum Width (mm)	1260
Carrier	n/a
Liner	81gsm single sided release glassine paper
Adhesive	A16
Other Information	Scrim reinforced minimum adhesion to steel 150gf/cm
Stripping Load (Release) (gf/cm)	5
Elongation at break, MD (%)	50
Elongation at break, TD (%)	30

Product Information correct as of 27th April 2015

**DelStar Technologies**

Broad Lane Gilberdyke East Yorkshire HU15 2TD

<http://extrudedfilmsandnets.co.uk> +44 (0)1430 440757

© DelStar Technologies Limited 2015. Registered in England #00592411

[Terms Of Use](#) [Disclaimer](#) [Accessibility](#) [Cookie Policy](#)