

Beige coloured scrim reinforced polyurethane/urethane film on paper carrier with a long history of use in medical applications



Beige coloured scrim reinforced polyurethane/urethane film on paper carrier with a long history of use in medical applications

### Typical Properties

Property	Typical Value
Thickness (Micron)	110
Weight (g/m <sup>2</sup> )	60
MVTR, upright (g/m <sup>2</sup> per 24hrs @37°C)	900
Tensile Strength MD (gf/cm)	1400
Tensile Strength TD (gf/cm)	900
Nominal Length at max width (lm)	1000
Minimum Width (mm)	50
Maximum Width (mm)	1290
Carrier	100gsm single sided release paper
Liner	n/a
Adhesive	n/a
Other Information	Scrim reinforced
Stripping Load (Release) (gf/cm)	1.3
Elongation at break, MD (%)	50
Elongation at break, TD (%)	30

Product Information correct as of 7th March 2018

### DelStar Technologies

Broad Lane Gilberdyke East Yorkshire HU15 2TD  
<http://extrudedfilmsandnets.co.uk> +44 (0)1430 440757

© DelStar Technologies Limited 2018. Registered in England #4296794

[Terms Of Use](#) [Disclaimer](#) [Accessibility](#) [Cookie Policy](#)